

CUSTOMER :
MODEL : MOG-2020-A4021
DESCRIPTION : LCD MODULE

◆ CUSTOMER APPROVAL

	CHECKED	CHECKED	APPROVAL
APPROVAL			
REMARK			

◆ SUPPLIER APPROVAL

PREPARED	CHECKED		APPROVAL

MYTECH CORPORATION

180 Old Tappan Rd., Bldg. 6, Old Tappan, NJ 07675

Tel: (201) 784-8867 Fax: (201) 784-8932

Email: mysales@mytechcorp.com

- NOTE:** 1. This specification may, wholly or partially, be subjected to change without notice.
2. Information contained herein is proprietary information of MYTECH CORPORATION. The dissemination use or duplication for any purpose other than for which the information is provided is prohibited by MYTECH CORPORATION except by express permission.

1. FEATURES

- 1) Number of dot ----- 200 x 200 dots
- 2) Display mode ----- STN-YELLOW
- 3) Display type ----- Transflective
- 4) Viewing direction ----- 6 o'clock
- 5) Operating temperature ----- Indoor
- 6) Drving voltage ----- Double power
- 7) Driving method ----- 1/200 duty
- 8) Type ----- QFP (Quad Flat Package)
- 9) Number of data line ----- 4-bit parallel
- 10) Appllicated IC ----- T6A39 & T6A40

2. MECHANICAL DATA

ITEM		WIDTH	HEIGHT	THICKNESS	UNIT
Module size		88.2	92.4	11.0	mm
Viewing area		72.0	72.0	-	mm
Dot	Size	0.28	0.28	-	mm
	Pitch	0.32	0.32	-	mm
Diameter of mounting hole		4-2.5			mm
Weight		About 70			g

3. ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	CONDITION	STANDARD VALUE		UNIT
			MIN.	MAX.	
Power supply for logic	$V_{DD}-V_{SS}$	$T_a=25^{\circ}\text{C}$	0	7.0	V
Power supply for LCD	$V_{DD}-V_{EE}$	$T_a=25^{\circ}\text{C}$	0	30.0	V
Input voltage	V_{IN}	$T_a=25^{\circ}\text{C}$	V_{SS}	V_{DD}	V
Operating temperature	T_{op}	-	0	50	$^{\circ}\text{C}$
Storage temperature	T_{STG}	-	-10	70	$^{\circ}\text{C}$

4. ELECTRICAL CHARACTERISTICS


ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
			MIN.	TYP.	MAX.	
Power supply for logic	V_{DD}	$T_a = 25^{\circ}\text{C}$	4.75	5	5.25	V
Input high voltage	V_{IH}	-	0.8	-	V_{DD}	V
Input low voltage	V_{IL}	-	V_{SS}	-	0.8	V
Output high voltage	V_{OH}	$I_{OH} = -0.5\text{mA}$	$V_{DD}-0.3$	-	V_{DD}	V
Output low voltage	V_{OL}	$I_{OL} = 0.4\text{mA}$	V_{SS}	-	0.3	V
Power supply current	I_{DD}	$V_{DD}=5.0\text{V}, V_{LCD}=21.5\text{V}$	-	12.0	20.0	mA
Power supply for LCD (Note 1) = V_{LCD}	$V_{DD}-V_L$	$T_a = 0^{\circ}\text{C}$	-	-	-	V
		$T_a = 25^{\circ}\text{C}$	-	21.5	-	V
		$T_a = 50^{\circ}\text{C}$	-	-	-	V

Note 1 : Power supply for LCD is available with R_L in accordance with contrast.


5. ELECTRO-OPTICAL CHARACTERISTICS (STN) (Ta = 25 °C)

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT	NOTE
Contrast ratio	K	1.5	3.0	-	-	3
Response time (rise)	T_r	-	200	350	ms	4
Response time (fall)	T_f	-	250	350	ms	4
Viewing angle	ϕ	-10 ~ 40			deg.	1.2
	θ	-40 ~ +40				


NOTE1. Definition of contrast K




NOTE2. Definition of optical response



NOTE3. Definition of angle θ and ϕ



NOTE4. Definition of viewing angle ϕ_1 and ϕ_2



6. QUALITY SPECIFICATION

6.1 Acceptable Quality Level

INSPECTION ITEM	SAMPLING PROCEDURES	A.Q.L
MAJOR	MIL-STD-105E Inspection Level II Normal Inspection Single sample inspection	1.0
MINOR	MIL-STD-105E Inspection Level II Normal Inspection Single sample inspection	2.5

Major defect :

A major defect is a defect that could result in failure or materially reduce that the usability of the unit of product for its intended purpose.

Minor defect :

A minor defect is one that does not materially reduce the usability of the product for its intended purpose or is a departure from established standards giving no significant bearing on the effective use or operation of the unit.

6.2 Inspection Conditions


6.2.1 The environmental conditions for inspection shall be as follows

- Room Temperature : $25 \pm 3^{\circ}\text{C}$
- Humidity Temperature : $65 \pm 20\% \text{RH}$

6.2.2 The external visual inspection


- The inspection shall be performed by using 40Watts fluorescent lamp for illumination and the distance between LCD and eyes of the inspector shall be 30cm or more.


6.3 Definition of the Area



- A area: Active Area
- B area: Viewing Area
- C area: Out of Viewing Area

6.4 Inspection Standards

Class of defects	Inspection Item	Criteria of defects		Remarks
MAJOR	Display on inspection	1) No Display 2) Abnormal Operation 3) Short Circuit 4) Pattern Open 5) Off Viewing angle		
	Missing	Component missing		
MINOR	Spot/Dent	Size	Defect size	Acceptable Number
		A Size	$\phi \leq 0.2 \text{ mm}$	Ignore
			$0.2 < \phi \leq 0.3 \text{ mm}$	1
			$\phi > 0.3 \text{ mm}$	0
		B Size	$\phi \leq 0.2 \text{ mm}$	Ignore
			$0.2 < \phi \leq 0.3 \text{ mm}$	2
			$\phi > 0.3 \text{ mm}$	0
	Cell Size (Viewing Area Criteria)			
	※ A size $< 2500\text{mm}^2$ Spot size = $(X+Y)/2$ B size $\geq 2500\text{mm}^2$			
				
Scratch	POSITIVE		NEGATIVE	
	Width X Length	Acceptable Number	Width X Length	Acceptable Number
	0.1 X 1.5 mm	3	0.1 X 1.5 mm	3
	0.08 X 3.0 mm	2	0.08 X 3.0 mm	2
	0.05 X 5.0 mm	1	0.05 X 5.0 mm	1
	※ Scratches should be separated more than 10mm each other			
Bubble	1) Round bubble should be treated as spot(positive) 2) Line bubble should be treated as scratch(positive)			

Class of defects	Inspection Item	Criteria of defects	Remarks
MINOR	Pattern Misalignment	Voids in segment 	
	Stain	Stains which cannot be removed even when wiped slightly with a soft cloth.	
	Rainbow	More than 2 colors are noticeable in the viewing direction.	
MINOR	PCB damage	Damage on gold or copper foil	
	Parts alignment	1) IC lead width is more than 50% beyond land pattern 2) Chip component is off center and more than 50% of the leads is off the pad out line.	
	Conductive foreignmatter (solderball, soldersplash)	Conductive foreign matter is not allowed	
	Bezel claw	Bezel claw missing or not bent	

7. RELIABILITY

ITEM	TEST	CRITERION
High temp.	70°C / 200 Hrs	* Total current consumption should be below double of initial value
Low temp.	-20°C / 200 Hrs	
High humidity	40°C X 90%RH / 200 Hrs	
Thermal shock	-20°C → 25°C → 70°C → 25°C / 5 Cycles (20min) (5min) (30min) (5min)	* Contrast ratio should be within initial value ±50%
Vibration	1.Operating time : Thirty minutes exposure for each direction(x,y,z) 2.Sweep frequency (1min) : 10Hz →55Hz →10Hz 3.Amplitude : 0.75mm	* No defect in cosmetic and operational function is allowable

* Remarks : Samples subjected to the tests shall be “ Not operating ” condition .


8. PIN CONNECTIONS

PIN NO.	SYMBOL	FUNCTION	
1	DB0	Data Bus Line	
2	DB1		
3	DB2		
4	DB3		
5	CP	Control signal for shifting data	
6	LO	Input for latch signal	
7	FLM	Input for shift clock pulse	
8	M	Input for frame signal	
9	VCC	+5V	Power supply for logic
10	GND	-	Ground
11	VEE	-16.5V	Operating voltage for LCD driving
12	NC	Non-connection	
13	NC	Non-connection	
14	NC	Non-connection	
15	NC	Non-connection	
16	EL	Power supply for EL	
17	EL	Power supply for EL	


11. TIMING CHARACTERISTICS

ITEM	SYMBOL	Min.	Max.	Unit
FP Pulse Width	t_{CWH}, t_{CWL}	95	-	nS
FP Rise/fall Time	t_r, t_f	-	30	nS
LP Set Up Time	t_{LRP}	20	-	nS
LP Hold Time	t_{LFP}	40	-	nS
LP Pulse Width	t_{LW}	40	-	nS
Data Set Up Time	t_{DSU}	20	-	nS
Data Hold Time	t_{DHD}	40	-	nS
E10 IN Set Up Time	t_{EIRP}	20	-	nS
E10 IN Hold Time	t_{EIFP}	40	-	nS
E10 IN Pulse Width	t_{EIW}	40	-	nS
E10 OUT Delay Time	t_{EOF}	-	100	nS
E10 OUT Hold Time	t_{EOH}	-	95	nS
FP Rise to LP Rise Time	t_{SL}	10	-	nS
LP Fall to FP Fall Time	t_{LS}	10	-	nS
FP Rise to E10 Rise Time	t_{SE}	10	-	nS
E10 Fall to FP Fall Time	t_{ES}	10	-	nS

DATA WRITE



DATA READ



12. PRECAUTION FOR USING

16.1 HANDLING

- 1) Refrain from storing mechanical shock and from applying any force to LCD MODULE.
It may cause mis_operation or damage of LCD.
- 2) Do not touch, press or rub the display panel with a hard, stiff tool or object as the polarizers in the panel are easily scratched.
- 3) If LCD is broken and liquid crystal material flow out, ingestion, inhalation, or contact with skin should be avoided. If liquid crystal material contact with skin, wash immediately with alcohol and rinse thoroughly with water.
- 4) Never use organic solvents to clear the display panel as these solvent may adversely affect the polarizer. To clean the display panel dampen a bit of absorbent cotton with petroleum benzene and gently wipe the panel, or contaminations by using a scotch tape.
- 5) Refrain from discharge of high electro-static voltage, it will damage C-MOS LSI in the MODULE.
- 6) Do not leave the MODULE in high temperature, especially in high humidity for a long time. It is recommended to store the MODULE where the temperature is in the range of 0°C to 35°C and the humidity is lower than 70%.
- 7) Store the MODULE without exposure to direct sunlight or fluorescent lamp.
- 8) Ultra violet cut filter is necessary for outdoor operation.
- 9) Avoid condensation of water, it may cause mis-operation or disconnection of electrode.

16.2 OPERATION

- 1) Never connect or disconnect the LCD MODULE from the main system while power is being supplied.
- 2) When supplying the M signal from the external unit to a GRAPHIC MODULE, set the duty to $50\% \pm 1\%$.
If the duty deviates too greatly from the value, a DC voltage will be applied to the liquid crystal, which could induce an electrochemical reaction and reduce the life of the MODULE.
- 3) Do not exceed the maximum rating values under the worst conditions taking account of the supply voltage variation, input voltage variation, and environmental temperature, etc. Otherwise LCD module may be damaged.

13. EXTERNAL DIMENSION

